



Light-Head with integrated power supply

- Omni directional low intensity light ( 10 cd).
- 4 optics with cover in hard polycarbonate and Powder-coated aluminum enclosure
- Simple installation
- LED drivers inside the Light-head with surge protections.
- Inbuilt Photocontroller

## Low Intensity Solar Based.

Electrical Characteristics	
Main voltage	12 VDC
Average wattage	>3W
Mechanical Characteristics	
IP degree	Ip65
Operating temperature	-20/+55°C
Weight	4 kg
Wire cross section	NA
Photometric Characteristics	
Effective light output day time at 0° on site	N/A
Effective light output twilight mode at 0° on site	N/A
Effective light output night mode at 0° on site	10 cd
Color day/twilight time	N/A
Color night time	red
Vertical beam spread	>10°
Horizontal beam spread	360°
Flash per minute	40

Note - Available in Steady Mode too.



31, Anandraj Industrial Estate.Sonapur Lane,  
Bhandup (W) Mumbai Maharashtra 400078



62, Raja Industrial Estate 1st Floor, P. K. Road,  
Mulund (W) Mumbai, Maharashtra 400080



+91 87798 25153, +91 81691 13218

+91 9372440178, +91 99871 60292



[info@enlightpro.com](mailto:info@enlightpro.com), [support@enlightpro.com](mailto:support@enlightpro.com)